

1.1 Gaussian and SI units

The two most widely used systems of units are the Gaussian system which uses centimeters, grams, and seconds for the fundamental quantities of length, mass, and time, and SI (Système International) which uses meters, kilograms and seconds for these quantities. When converting from Gaussian to SI units numerical values are related by the scaling factors

$$x_G = k_x x_{SI}, \quad m_G = k_m m_{SI}, \quad t_G = t_{SI}$$

where $k_x = 100$ and $k_m = 1000$. Consider, for example, energy which has units of $x^2 s^{-2} m$. If the numerical value is U_G in the Gaussian system then in SI units the energy is related by

$$U_G \sim x_G^2 m_G \rightarrow (k_x^2 k_m) x_{SI}^2 m_{SI} \sim (k_x^2 k_m) U_{SI}.$$

Thus

$$U_{SI} = \frac{1}{k_x^2 k_m} U_G = 10^{-7} U_G$$

which agrees with the known relation $1 \text{ erg} = 10^{-7} \text{ J}$.

While it is easy to transform quantities such as energy between the systems, when dealing with electromagnetism confusion can arise since the same physical quantities have different units as well as different numerical values in the two systems. The Maxwell equations, constitutive relations between fields and polarizations, and Lorentz force per charge q in Gaussian units are

$$\begin{aligned} \nabla \times \mathbf{E} &= -\frac{1}{c} \frac{\partial \mathbf{B}}{\partial t}, & \nabla \times \mathbf{H} &= \frac{1}{c} \frac{\partial \mathbf{D}}{\partial t} + \frac{4\pi}{c} \mathbf{J}, \\ \nabla \cdot \mathbf{D} &= 4\pi \rho, & \nabla \cdot \mathbf{B} &= 0, \\ \mathbf{D} &= \mathbf{E} + 4\pi \mathbf{P}, \\ \mathbf{H} &= \mathbf{B} - 4\pi \mathbf{M}, \\ \mathbf{F} &= q \left(\mathbf{E} + \frac{\mathbf{v}}{c} \times \mathbf{B} \right). \end{aligned}$$

In the SI system the equations are

$$\begin{aligned} \nabla \times \mathbf{E} &= -\frac{\partial \mathbf{B}}{\partial t}, & \nabla \times \mathbf{H} &= \frac{\partial \mathbf{D}}{\partial t} + \mathbf{J}, \\ \nabla \cdot \mathbf{D} &= \rho, & \nabla \cdot \mathbf{B} &= 0, \\ \mathbf{D} &= \epsilon_0 \mathbf{E} + \mathbf{P}, \\ \mathbf{H} &= \frac{1}{\mu_0} \mathbf{B} - \mathbf{M}, \\ \mathbf{F} &= q (\mathbf{E} + \mathbf{v} \times \mathbf{B}). \end{aligned}$$

In SI the constants ϵ_0, μ_0 have exact values

$$\epsilon_0 \mu_0 = \frac{1}{c^2}, \quad \mu_0 = 4\pi \times 10^{-7}, \quad c = 299792458 \text{ m/s}.$$

To convert any electromagnetic equation from Gaussian to SI units we multiply by the scaling factors

$$\begin{aligned}\mathbf{E} &\rightarrow k_E \mathbf{E}, & \mathbf{D} &\rightarrow k_D \mathbf{D}, \\ \mathbf{B} &\rightarrow k_B \mathbf{B}, & \mathbf{H} &\rightarrow k_H \mathbf{H}, \\ \mathbf{P} &\rightarrow k_P \mathbf{P}, & \mathbf{M} &\rightarrow k_M \mathbf{M}, \\ \rho &\rightarrow k_\rho \rho, & \mathbf{J} &\rightarrow k_J \mathbf{J}.\end{aligned}$$

Consistency of the Maxwell equations and the Lorentz force law in the two systems fixes the scaling constants to be

$$\begin{aligned}k_E &= \sqrt{4\pi\epsilon_0}, & k_D &= \sqrt{\frac{4\pi}{\epsilon_0}}, \\ k_B &= \sqrt{\frac{4\pi}{\mu_0}}, & k_H &= \sqrt{4\pi\mu_0}, \\ k_\rho &= k_J = k_P = \frac{1}{\sqrt{4\pi\epsilon_0}}, \\ k_M &= \sqrt{\frac{\mu_0}{4\pi}}.\end{aligned}$$

As an example to convert the Coulomb potential energy of an electron from Gaussian to SI units we use

$$\frac{e_G^2}{r_G} = (k_x^2 k_m) \frac{k_\rho^2 e_{SI}^2}{r_{SI}}.$$

Thus the electron charge in Gaussian units is related to the charge in SI units (1.602×10^{-19} C) by

$$e_G = e_{SI} \sqrt{k_x^2 k_m} \times k_\rho \times \sqrt{\frac{r_G}{r_{SI}}} = e_{SI} \times c \times 10 = 4.803 \times 10^{-10} \text{ esu}$$

where esu stands for electrostatic units.